



EC-TYPE EXAMINATION CERTIFICATE

Equipment or Protective System Intended for use in Potentially Explosive Atmospheres
Directive 94/9/EC

3 EC-Type Examination Certificate Number : BAS01ATEX7159

4 Equipment or Protective System: MTL5053 - 31.25Kbits/s FIELDBUS ISOLATOR/POWER SUPPLY

5 Manufacturer: MEASUREMENT TECHNOLOGY LIMITED

6 Address: Luton, Bedfordshire, LU1 3JJ

- This equipment or protective system and any acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.
- The Electrical Equipment Certification Service, notified body number 600 in accordance with Article 9 of the Council Directive 94/9/EC of 23 March 1994, certifies that this equipment or protective system has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment and protective systems intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in confidential Report No

01(C)0220 dated 18 December 2001 (held on EECS 0703/02/299)

9 Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

EN 50014: 1997 + Amds 1 & 2 EN 50020: 1994

except in respect of those requirements listed at item 18 of the Schedule.

- If the sign "X" is placed after the certificate number, it indicates that the equipment or protective system is subject to special conditions for safe use specified in the schedule to this certificate.
- This EC-TYPE EXAMINATION CERTIFICATE relates only to the design and construction of the specified equipment or protective system. If applicable, further requirements of this Directive apply to the manufacture and supply of this equipment or protective system.
- 12 The marking of the equipment or protective system shall include the following:-

 $\langle E \rangle$ II (1) GD [EEx ia] IIC (-20°C \leq T_a \leq +60°C)

This certificate may only be reproduced in its entirety and without any change, schedule included.

File No: EECS 0703/02/334

This certificate is granted subject to the general conditions of the Electrical Equipment Certification Service. It does not necessarily indicate that the apparatus may be used in particular industries or circumstances.



Electrical Equipment Certification Service
Health and Safety Executive
Harpur Hill, Buxton, Derbyshire, SK17 9JN, United Kingdom
Tel: +44(0)1298 28000 Fax: +44(0)1298 28244
internet: www.baseefa.com e-mail: baseefa.info.eecs@hsl.gov.uk



I M CLEARE DIRECTOR 29 April 2002



13 Schedule

14 EC-TYPE EXAMINATION CERTIFICATE Nº BAS01ATEX7159

15 Description of Equipment or Protective System

The MTL5053 - 31.25KBit/s Fieldbus Isolator/Power Supply is designed to restrict the transfer of energy from an unspecified safe-area apparatus to an intrinsically safe circuit by the limitation of voltage and current.

Isolation of the non-hazardous and hazardous area circuits is achieved using a galvanically isolating transformers and an optocoupling device and these components, along with other electronic components, are mounted on a printed circuit board (pcb) which is housed in a plastic enclosure. Colour coded terminals are provided for making external connections.

CON 3, Pins 7, 8, 9; CON 4, Pins 10, 11, 12 and CON 5, Pins 13 &14

 $U_{\rm m} = 250 \rm V$

The circuit connected to the safe area terminals on CON 3, CON 4 and CON 5 are designed to operate from a d.c. supply voltage of up to 35V.

CON 1 pin 2, CON 2 Pin 5 w.r.t. CON 1 pin 1, CON 2 pin 4

 $U_0 = 22 \text{V}$

 $I_0 = 216 \text{mA}$

 $I_{\rm o} = 1.2 {\rm W}$

 $C_{\rm i}=0$

 $L_{\rm i} = 0$

The capacitance and either the inductance or the inductance to resistance ratio (L/R) of the hazardous area load must not exceed the following values:

GROUP	CAPACITANCE in µF	INDUCTANCE in mH	OR	L/R RATIO in µH/ohm
IIC	0.165	0.26		31
IIB	1.140	0.79		132
IIA	4.200	2.12		266

Equipment referred to in this certificate having the same type number as items in BASEEFA Certificate No Ex 97D2193 may be used as a direct substitute in a system provided that the cable parameters used are within the limits shown on this certificate.

VARIATION 0.1

To permit the connection of MTL5000 Ring Terminal assemblies in place of the safe and hazardous area screw terminals. The enclosure remains IP20 whether or not the Ring Terminal is fitted. The following MTL5000 Ring Terminals may be connected to the MTL5053. Blanking covers may be removed if necessary.

Page 2/4



13 Schedule

14 EC-TYPE EXAMINATION CERTIFICATE Nº BAS01ATEX7159

Hazardous Area Terminal	MTL5053 pins	1, 2, 4, 5
	HAZ-RT-1-5	1, 2, 3, 4
G-G-AT	MTL5053 pins	8, 9
Safe Area Terminal	SAF-RT-8-9	5, 6

16 Report No

01(C)0220

17 Special Conditions For Safe Use

None.

18 Essential Health and Safety Requirements

Clause	Subject	Compliance
1.1.3	Changes in characteristics of materials and combinations thereof	Report No 01(C)0220 Clause 5.1.1.3
1.2.2	Components for incorporation or replacement	Report No 01(C)0220 Clause 5.1.2.2
1.2.5	Additional means of protection	Report No 01(C)0220 Clause 5.1.2.5
1.2.7	Protection against other hazards	Report No 01(C)0220 Clause 5.1.2.7
1.4.2	Withstanding attack by aggressive substances	Report No 01(C)0220 Clause 5.1.4.2

19 DRAWINGS

Number	Sheet	Issue	Date	Description
CI5053-1	1	1	04.97	MTL5053 Parts List
CI5053-1	2	1	04.97	MTL5053 Circuit Diagram
CI5053-1	3	2	12.01	MTL5053 Component Layout
CI5053-1	4	2	12.01	MTL5053 General Assembly
CI5053-1	5	1	04.97	MTL5053 PCB Track Layout
CI5053-1	6	1	04.97	MTL5053 Transformer Winding Details
*CI4000-1	1	2	11.92	MTL4000 Series 2-core IS Transformer
*CI4000-1	2	2	11.92	MTL4000 Series 2-core IS Transformer

Drawings marked * are associated with and are held on BASEEFA Certificate BAS01ATEX7163



13 Schedule

14 EC-TYPE EXAMINATION CERTIFICATE Nº BAS01ATEX7159

Drawing associated with Variation 0.1

Number	Sheet	Issue	Date	Description
**CI5000-12	1 to 4	1	02.02	MTL5000 Ring Terminal

Drawing marked ** is associated with and held on BASEEFA Certificate BAS01ATEX7144

This certificate may only be reproduced in its entirety and without any change, schedule included.

BASEEFA List Keywords
2ISOLBAR