



- NOTES:-
- EX e TYPE, 1.2mm THICK, STAINLESS STEEL 316L ENCLOSURE WITH SCREW FIXED COVER.
 - EXTERNAL M10 EARTH STUD FITTED, WITH EARTH STRAP TO LID.
 - IP66 Ex e CERTIFIED NICKEL PLATED BRASS BREATHING PLUG FITTED. 14 FURTHER POSITIONS DRILLED M20 CLEARANCE FOR TRUNK AND SPUR CONNECTION CABLE GLANDS IN BOTTOM FACE OF ENCLOSURE. SYSTEM SUPPLIED WITH THESE POSITIONS FITTED WITH IP66 Ex e CERTIFIED NICKEL PLATED BRASS STOP PLUGS.
 - PRODUCT LABEL FITTED ON OUTSIDE OF LID.
 - APPROPRIATE CABLE GLANDS TO BE FITTED WHERE REQUIRED.
 - SEE INSTRUCTION MANUAL INM937x-FB2-Px-SS FOR INSTALLATION INSTRUCTIONS.
 - WITH REGARD TO THE DOCUMENT TITLE, THE "...9373-FB2-Px-SS" REFERENCE COVERS THE "...9373-FB2-PC-SS, PLUGGABLE SPRING CLAMP" VARIANT AND THE "...9373-FB2-PS-SS PLUGGABLE SCREW TERMINAL " VARIANT.
 - THIS DRAWING IS REPRESENTATIVE, BUT ACTUAL PRODUCT MAY DIFFER IN DETAIL.

Date	Modification	 <div>Eaton Electric Limited, Great Marlings, Butterfield, Luton, Bedfordshire, England, LU2 8DL Telephone: +44 (0)1582 723633 Web: www.mtl-inst.com Email: mtlenquiry@eaton.com</div>	This component / assembly to be in compliance with RoHS & REACH regulations.			Sheet: 1 of 1	
2.17			Tolerance (Unless Otherwise Stated): N/A		Scale: 1:2	Drawn by: OB	Drawn Date: 06.16
		This drawing and any information or descriptive material set out on it are the confidential and copyright property of Eaton Electric Limited and MUST NOT BE DISCLOSED, COPIED, LOANED in whole or part or used for any purpose without the written permission of Eaton Electric Limited.	Title: CUSTOMER DRAWING 9373-FB2-Px-SS		Drawing Number: CD9373-111		Revision: 2