MTL4581 – MTL5581 MILLIVOLT/THERMOCOUPLE ISOLATOR

for low-level signals


The MTLx581 takes a low-level dc signal from a voltage source in a hazardous area, isolates it, and passes it to a receiving instrument located in the safe area. The module is intended for use with thermocouples utilising external cold-junction compensation. A switch enables or disables the safety drive in the event of thermocouple burnout or cable breakage; a second switch permits the selection of upscale or downscale operation as appropriate.

SPECIFICATION


See also common specification

Number of channels One Signal source Any dc millivolt source Location of millivolt source Zone 0, IIC, T4-T6 hazardous area if suitably certified Div. 1, Group A, hazardous location Input and output signal range 0 to \pm 50mV, overrange to \pm 55mV Maximum lead resistance 600Ω **Output resistance** 60Ω nominal Transfer accuracy@20°C Linearity and repeatability < 0.05% of reading or \pm 5µV, whichever is the greater **Temperature drift** < 2µV/°C, maximum **Response time** Settles to within 10% of final value within 150µs Frequency response dc to 4kHz nominal Safety drive on THC burnout Two switches enable or disable the safety drive and select upscale or downscale operation

MTL4581



MTL5581



LED indicator

Green: power indication Power requirement, Vs 30mA max, 20V dc to 35V dc Power dissipation within unit

0.7W typical at 24V 0.91W at 35V Safety description

Terminals 1 to 2

Non-energy-storing apparatus \leq 1.5V, \leq 0.1A and \leq 25mW; can be connected without further certification into any IS loop with an open-circuit voltage <28V



Eaton Electric Limited, Great Marlings, Butterfield, Luton Beds, LU2 8DL, UK. Tel: + 44 (0)1582 723633 Fax: + 44 (0)1582 422283 E-mail: mtlenguiry@eaton.com www.mtl-inst.com The given data is only intended as a product description and should not be regarded as a legal warranty of properties or guarantee. In the interest of further technical developments, we reserve the right to make design changes

© 2016 Eaton All Rights Reserved Publication No. EPSx581 Rev4 010916 EUROPE (EMEA): +44 (0)1582 723633 mtlenquiry@eaton.com THE AMERICAS: +1 800 835 7075 mtl-us-info@eaton.com ASIA-PACIFIC: +65 6 645 9888 sales.mtlsing@eaton.com