

MTL GIR250

Dual range analyser for oxygen and carbon dioxide

- **Dual measurement of oxygen and carbon dioxide in one instrument**
- **Compact, robust unit**
- **Transportable laboratory style case**
- **Simple, easy to read display**
- **Intuitive user interface**
- **Easy calibration process**
- **Pump and flowmeter for sample control**
- **Comprehensive set of programmable alarm relays and analogue outputs**
- **Real time results**
- **Fast sensor response**

Typical Applications include:

- **Respiration measurement**
- **Fermentation monitoring**
- **Douglas bag analysis**
- **Sports science**



The GIR250 is designed to monitor percentage levels of oxygen and carbon dioxide in a single, robust unit.

Based on our galvanic (electrochemical) cell measuring principle for oxygen measurement, and the infra-red principle for carbon dioxide, the GIR250 provides a permanent display of both gases up to a resolution of 0.01%. The instrument can be pre-programmed with pass/fail criteria for each of the gases, and results can be transferred to external recording/logging devices using the 4-20mA outputs.

The key design philosophy is to provide a simple to use, reliable instrument providing accurate repeatable results over the whole of its range. Calibration is very simple using the front panel keypad and can be carried out with little or no training.

Cost of ownership is very low, containing a non-depleting infra-red sensor and a user-serviceable replacement galvanic cell.

Ease of use and reliability—a good combination.

MTL GIR250 dual range analyser

February 2017

SPECIFICATION

Ranges, resolution and accuracy:

Oxygen:

Range: 0-100%

Resolution: 0.1%

Accuracy \pm 2% of span

Carbon Dioxide:

Range: 0-10%

Resolution: 0.1%

Accuracy \pm 2% of span

Range: 0-25%

Resolution: 0.01%

Accuracy \pm 2% of span (5% to 100% scale)

Speed of response

Typically:

Oxygen 15 seconds

Carbon dioxide 20 seconds

Sample Conditions

Flow 100 – 300 ml/min

Pressure Set by vent pressure (nominally atmospheric)

Temperature -5 – 40°C (non,condensing)

Analogue Outputs:

4,20mA for both gases. Programmable to be proportional to anywhere between 0/20% and 0/100% of span. Maximum load 1000 ohms per output.

Alarm Relay Outputs

Two alarms per gas, programmable to be OFF, HIGH, or LOW. The hysteresis is also user programmable. Rated at 48v AC or DC at 0.5 amp.

Sample Connections, inlet and outlet

Inlet and outlet 0.25" (suitable for 6mm) diameter tube. Both ports are fitted with captive seal compression fittings.

Ambient temperature

-5°C to 40°C

Power supply requirements

220 to 240v at 50 to 60Hz.

Power consumption

36VA

Enclosure

Free standing case 255W x 170H x 260D, dimensions do not include case fittings.

Weight

6.0kg approximate



Eaton Electric Limited,
Great Marlings, Butterfield, Luton
Beds, LU2 8DL, UK.
Tel: + 44 (0)1582 723633 Fax: + 44 (0)1582 422283
E-mail: mtlgas@eaton.com
www.mtl-inst.com

© 2017 Eaton
All Rights Reserved
Publication No. EPS MTL GIR250 500-0098 Rev 2
February 2017

EUROPE (EMEA):
+44 (0)1582 723633
mtlenquiry@eaton.com

THE AMERICAS:
+1 800 835 7075
mtl-us-info@eaton.com

ASIA-PACIFIC:
+65 6 645 9888
sales.mtlsing@eaton.com

The given data is only intended as a product description and should not be regarded as a legal warranty of properties or guarantee. In the interest of further technical developments, we reserve the right to make design changes.